

MMX452-BKT

Best in Class

The Mobile Multimedia Solution consists of the Optoma EDX452-BKT, a DVD/VCR player, an AN-130 speaker, and a cart.

This equipment makes up a complete presentation package for the classroom or conference room. The items are installed and locked on the cart for security (as shown in the pictures), with brackets included for speaker, DVD/VCR and projector.

Optoma's EDX452-BKT is designed to meet the demanding requirements of school districts and businesses. Bright, high contrast images provide easy-to-read text, and the built-in closed captioning decoder displays text from videos that have closed captioning embedded in the signal. Wired networking allows remote management and control of the projector, and a built-in 10-watt speaker system outputs volume required for larger audiences. Included in this package is a host of cables allowing you flexibility in your classroom or boardroom.



Specifications

Display Technology:

Single 0.55" DMD DLP® Technology by Texas Instruments

Resolution: Native XGA (1024 x 768)

Maximum Resolution: UXGA (1600 x 1200)

Brightness (Typical): 2800 ANSI Lumens

Contrast Ratio: 3000:1 (Full On/Full Off)

Lamp Life and Type: 4,000/3,000 hours (STD/Bright) 180W P-VIP lamp

Throw Ratio: 1.6 to 1.92:1 (Distance/Width)

Projection Distance: 3.93 to 32.8 feet (1.2 to 10 meters)

Remote Control: Fully Featured IR Remote with Laser Pointer and Mouse

Audio: Two 5-Watt Stereo Speakers

Weight: 6.4 pounds (2.9 kg)

Computer Compatibility:

UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility: NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

Horizontal Scan Rate: 15.3 to 91.4 kHz

Vertical Refresh Rate: 25 to 85 Hz

Keystone Correction: ±40° Vertical

Projection Lens: F=2.4~2.66, f=18.2~21.8mm, 1.2x Manual Zoom and Focus

I/O Connectors: HDMI, Two VGA-In, VGA-Out, S-Video, Composite Video, Three Stereo Audio-In, Stereo Audio-Out, RJ45, RS-232 and USB

Security: Kensington® Lock, Security Bar and Keypad Lock

Projection Method: Front, Rear, Ceiling Mount, Table Top

User Controls:

Complete On-Screen Menu Adjustments in 23 Languages

Dimensions (W x H x D): 12.76 x 3.82 x 9.21 inches (324 x 97 x 234 mm)

Noise Level: 29dB/34dB (STD/Bright)

Power Consumption: 255 Watts (Bright), 233 Watts (STD) <1 Watt (standby mode)

Standard Accessories: AC power cord, 25' VGA to VGA Cable, VGA-Y Cable/Splitter, Remote Control, Batteries for Remote, USB Cable, Carrying Case, Lens Cap, CD-ROM User's Manual and Guides

Optional Accessories: Ceiling Mount, 15-pin to 3 RCA component/ HDTV adapter, S-video cable, 3002 Distribution Amp (for long runs), 4010 Tuner Converter (converts all signals to XGA), Powered Speaker

Warranty: 3 Years Optoma Express Replacement Service, 1 Year on lamp